







Application Guideline



Emulsion (Paste) PVC Resin Siamvic® (by Emulsion & Micro-suspension Polymerization)

Process	360NA	367NK	370HD	372LD	167GZ
Coating 	●	●	●	●	●
Molding 				●	●
Spraying 			●		●
Dotting 			●		●
Blending with suspensin & emulsion 					●
Application  www.agcvinythai.com	<ul style="list-style-type: none"> ▪Carpet backing ▪Adhesive ▪Conveyor belt ▪Plastisol ink ▪Automotive underbody coating and sealants 	<ul style="list-style-type: none"> ▪Artificial leather ▪Canvas ▪Wall covering ▪Floor covering ▪Sealants 	<ul style="list-style-type: none"> ▪Artificial Leather ▪Conveyor Belt ▪Automotive underbody coating and sealants ▪Dotted gloves ▪Plastisol Ink 	<ul style="list-style-type: none"> ▪Artificial leather ▪Tarpaulin, canvas ▪Table cloth ▪Curtain ▪Conveyor belt ▪Coil coating ▪Carpet backing ▪Toy ▪Crown cork seal ▪Tool handle 	<ul style="list-style-type: none"> ▪Blending in SPVC -provides a processing aid effect -speeds up fusion ▪Blending in EPVC -lower plastisol viscosity -reduces dilatancy

● Recommended ● Acceptable for use