







Application Guideline



Emulsion (Paste) PVC Resin Siamvic®

(by Emulsion & Micro-suspension Polymerization)

Process	360NA	367NK	370HD	372LD	167GZ
Coating 	●	●	●	●	
Molding 		●		●	
Spraying 			●		
Dotting 			●	●	
Blending with suspension & emulsion 					●
Application  www.agcvinythai.com	<ul style="list-style-type: none"> ▪ Carpet backing ▪ Adhesive ▪ Conveyor belt ▪ Plastisol ink ▪ Automotive underbody coating and sealants 	<ul style="list-style-type: none"> ▪ Artificial leather ▪ Canvas ▪ Wall covering ▪ Floor covering ▪ Sealants 	<ul style="list-style-type: none"> ▪ Artificial Leather ▪ Conveyor Belt ▪ Automotive underbody coating and sealants ▪ Dotted gloves ▪ Plastisol Ink 	<ul style="list-style-type: none"> ▪ Artificial leather ▪ Tarpaulin, canvas ▪ Table cloth ▪ Curtain ▪ Conveyor belt ▪ Coil coating ▪ Carpet backing ▪ Toy ▪ Crown cork seal ▪ Tool handle 	<ul style="list-style-type: none"> ▪ Blending in SPVC -Provides a processing aid effect -Speed up fusion ▪ Blending in EPVC - Lower plastisol viscosity - Reduces dilatancy

● Recommended

● Acceptable for use



AGC VINYTHAI