## **Application Guideline**



## Emulsion (Paste) PVC Resin Siamvic®

(by Emulsion & Micro-suspension Polymerization)

_	(by Emulsion & Micro-suspension Polymerization )				
Process	360NA	367NK	370HD	372LD	167GZ
Coating	•	•	•	•	
Molding		•		•	
Spraying			•		
Dotting			•	•	
Blending with suspension & emulsion					•
Application					
	<ul> <li>Carpet backing</li> </ul>	<ul> <li>Artificial leather</li> </ul>	<ul> <li>Artificial Leather</li> </ul>	<ul> <li>Artificial leather</li> </ul>	- Blending in
	<ul><li>Adhesive</li></ul>	<ul><li>Canvas</li></ul>	<ul> <li>Conveyor Belt</li> </ul>	<ul><li>Tarpaulin,canvas</li></ul>	SPVC
	<ul> <li>Conveyor belt</li> </ul>	Wall covering	<ul> <li>Automotive</li> </ul>	■ Table cloth	- Provides a
	<ul> <li>Plastisol ink</li> </ul>	Floor covering	underbody coating	<ul> <li>Curtain</li> </ul>	processing aid effect
	<ul> <li>Automotive</li> </ul>	■ Sealants	and sealants	<ul> <li>Conveyor belt</li> </ul>	- Speed up fusion
	underbody coating		<ul> <li>Dotted gloves</li> </ul>	<ul> <li>Coil coating</li> </ul>	Blending in
	and sealants		<ul> <li>Plastisol Ink</li> </ul>	<ul> <li>Carpet backing</li> </ul>	EPVC
				■ Toy	- Lower plastisol
www.agcvinythai.com				Crown cork seal	viscosity
*********agoviiiytiiai.coiii				■ Tool handle	- Reduces dilatancy

Recommended

Acceptable for use

